

GRATE
WEIGHT: 266 LBS



DETAIL "A"



SECTION A-A



SECTION B-B



FRAME
WEIGHT: 160 LBS



SECTION C-C



SECTION D-D



NOTES:

1. FURNISH GRATE AND FRAME IN EITHER DUCTILE IRON (ASTM A 536 GRADE 60) OR CAST GRAY IRON: AASHTO M 105, CLASS 30B (ASTM A 48).
2. INSTALLATION REQUIRES SUPPORT UNDER LONGITUDINAL AXIS OF FRAME, ORIENT GRADE WITH DIRECTION OF FLOW.

DESIGN DATA

MS 18 (HS-20) OR INTERSTATE ALTERNATE LOADING IN ACCORDANCE WITH CURRENT AASHTO AND INTERIM SPECIFICATIONS.

DUCTILE IRON AND STRUCTURAL STEEL: fs = 20,000 psi

NO.	DATE	APPR.	REMARKS

REVISIONS

UTAH DEPARTMENT OF TRANSPORTATION
STANDARD DRAWINGS FOR ROAD AND BRIDGE CONSTRUCTION
SALT LAKE CITY, UTAH

RECOMMENDED FOR APPROVAL — JAN.01,2008 DATE

CHAIRMAN STANDARDS COMMITTEE APPROVED — JAN.01,2008 DATE

DEPUTY DIRECTOR

DIRECTIONAL FLOW GRATE AND FRAME

STANDARD DRAWING TITLE

STD DWG
GF 4

DGN File:L:\Standard Drawings\Imperial\2008Approved\Grates Frames and Trash Racks (GF)\GF04.dgn

18-DEC-2007